

Telephone, Ethernet & Data Fiber Optic Multiplexer

Model TC8520

- Multiplexes 10/100 Ethernet, 2-Wire Analog POTS and Optional RS-232, RS-422, TTL, Dry Contact
- Network Management (Web, Telnet)
- One Fiber Bi-Directional Communication Optic Option
- Multimode or Single Mode (1300/1550nm)
- Power Redundancy, Optical Redundancy Optional
- 12VDC, Optional 24VDC, -48VDC, 125VDC or 115/230VAC
- Industrial Hardened (optional)
- Hi-Temp2 Version Exceeds NEMA & Caltrans Traffic Control Specs



TC8520P 19" Wide, 1U High Rackmount Version

The TC8520 Telephone, Ethernet & Data Fiber Multiplexer multiplexes various combinations of 2-wire Analog POTS, 1 Ch. 10/100 Ethernet or Serial Data channels over single mode (1300/1550nm) or multimode fiber (1300/1550nm).

The TC8520 supports distances to more than 100 km and offers one fiber bi-directional optic option communication option to maximize fiber cable usage. Optional redundant power and optics include automatic switchover for maximum reliability.

Setup, diagnostics and control is accessed via Serial Terminal, Telnet management ports. Diagnostics include LED indicators, dry contact alarms and local and remote loopback.

The Ethernet port supports full 10Mbps bandwidth and rate control in increments of 32Kbps. It is IEEE 802.3/802.3u/802.3x compliant.

The TC8520 converts 2-wire FXS to fiber optics on the telephone side with ring down capability and FXO on the PBX side. Because the TC8520 digitizes the analog signals (PCM), voice quality does not degrade over extended distances. Serial interface options are RS-232, RS-422, TTL, Dry Contact.

The TC8520 is available basic standalone or 1U high "pizza box." Fiber optic connectors are ST, FC or SC. Standard power is 12VDC and includes built-in redundancy. Optional power sources include 24VDC, -48VDC, 125VDC or 115/230VAC with an external power cube. High temperature (-20°C to 70°C) and extreme temperature (-40°C to 80°C) versions are also available.



Applications

Typical applications include extending SDH/SONET backbones and adding Telephone Voice, Ethernet and Serial service to existing fiber optic links. Service Providers use the TC8520 as an efficient, cost effective method to provide their customers with Telephone Voice, Ethernet and Serial connections. The one fiber bi-directional communication, option can double usage of existing fiber optic cable plants.

TC Communications, Inc.
17881 Cartwright Rd. Irvine, CA 92614 U.S.A.
Tel: (949) 852-1972, Fax: (949) 852-1948
Sales: (800) 569-4736
Web Site: www.tccomm.com
E-mail: sales@tccomm.com



Typical Application Using TC8520 Telephone, 10/100 Ethernet & Serial Data Fiber Optic Multiplexers

Data Rates

Telephone.....300Hz to 3.4 KHz
 Ethernet10/100 Mbps
(10 Mbps throughput)
 RS-232Up to 128 Kbps Async
64 Kbps Sync
 RS-422, TTLUp to 19.2Kbps

Channel Capacity

Telephone.....4
 Ethernet.....1
 RS-232, RS-422, TTL4

Optical

Transmitter.....ELED/LASER*
 ReceiverPIN Diode
 Wavelength
1300nm Multimode
1300/1550nm Single Mode
 Optical Connectors.....ST , FC, SC
 Loss Budgets* -
 LED/ELED.....15dB MM @62.5/125µm
 LASER.....20dB SM @9/125µm

Electrical

Interface.....2-wire Analog POTS
IEEE 802.3 Ethernet
RS-232, RS-422, TTL
 Ethernet Connector.....RJ45F
 2-wire Analog Connector.....RJ11F
 RS-232, RS-422, TTL.....RJ45

System

Bit Error Rate1 in 10¹⁰ or Better

Visual Indicators

System LEDs.....PWR A, PWR B, Vcc
 Channel Status (each port).....RXD,
RLOS, LOS, RLPB, BPV, Alarm
 Optical Signal StatusSyncB
Optic in Use, RXA, RXB, VLIN

Diagnostic Functions

Local and Remote Loopback

Power

Standard12VDC @ 1.2A
 Optional24VDC, -48VDC,
125VDC, 115/230VAC

Temperature

Operating.....-10°C to 50°C
 Hi-Temp1 (optional)-20°C to 70°C
 Hi-Temp2 (optional)-40°C to 80°C
 Storage.....-40°C to 90°C
 Humidity.....95% non-condensing

Physical (Standalone Unit)

Height.....(6.70 cm) 2.6"
 Width.....(18.14 cm) 7.1"
 Depth.....(24.8 cm) 9.8"
 Weight.....(1.36 kg) 3.0 lbs

*Contact factory for higher requirements

** Future release



ISO 9001
 QMI-SAI Global
 #1045959

TC Communications, Inc.
 17881 Cartwright Road
 Irvine, CA 92614 U.S.A.
 Factory Tel: (949) 852-1972
 Fax: (949) 852-1948

Sales Office
 U.S.A. Domestic International
 (800) 569-4736 (949) 852-1973

Web Site: www.tccomm.com
 E-mail: sales@tccomm.com