


100/140/500 Graded-Index Optical Fiber

P/N: BF04432-02



Overview

This graded-index 100/140 μm multimode fiber has a 100 μm core diameter and a 140 μm cladding diameter. The fiber is designed for use at 850 nm and/or 1300 nm. It has a 500 μm dual UV acrylate buffer.

The large core diameter and high Numerical Aperture make this fiber suitable for use in applications where high coupling efficiency to a light source is necessary: industrial systems and transportation platforms, for example.

Typical Applications

Aerospace and Avionics
Communications



A Furukawa Company

100/140/500 Graded-Index Optical Fiber

P/N: BF04432-02

Product Specifications	
Product Description	100/140/500 Optical Fiber
Physical Characteristics	
Coating Material	Dual UV Acrylate
Core Diameter	100 ± 4 μm
Cladding Diameter	140 ± 3 μm
Coating Diameter	500 ± 25 μm
Core/Clad Offset	≤ 3 μm
Core Non-Circularity	≤ 5%
Clad Non-Circularity	≤ 2.0%
Crimp & Cleave Compatible	No
Optical Characteristics	
Type	Multimode Graded-Index
Numerical Aperture	0.29
Bandwidth @ 1300 nm	≥ 100 MHz-km
Bandwidth @ 850 nm	≥ 100 MHz-km
Attenuation @ 1300 nm	≤ 1.5 dB/km
Attenuation @ 850 nm	≤ 4 dB/km
Mechanical and Environmental	
Operating Temperature	-40 to +85 °C
Short-Term Bend Radius	≥ 11 mm
Long-Term Bend Radius	≥ 19 mm
Proof Test Level	100 kpsi (0.689 GPa)
Order by Part Number	BF04432-02
Product Description Code	ACU-MC100D
OPTIONS: Cabling	

For additional information please contact your sales representative.

You can also visit our website at www.ofsoptics.com or call 1-888-fiberhelp (1-888-342-3743) USA or 1-770-798-5555 outside the USA.



Copyright © 2019 OFS Fitel, LLC.
All rights reserved, printed in USA.

OFS Marketing Communications
Date: 11/19



OFS reserves the right to make changes to the prices and product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any OFS warranties or specifications relating to any of its products or services.