

## **LC Crimp & Cleave Termination Kit**

P/N: DT03732-LC1



## **Overview**

With the LC termination kit, Graded-Index HCS® (GiHCS®) Optical Fiber in 50/230, 62.5/230, and the original Step-Index HCS 200/230 µm sizes can be field terminated with LC connectors. Easy to learn and quick to connect! Associated insertion loss test kits measure performance after termination.





P/N: DT03732-LC1

Product Specifications	
Product Description	LC Crimp & Cleave Termination Kit
Compatibility	
For Use with Connector Types	P26763-01, LC Crimp & Cleave Connector
	P26763-02, LC Crimp & Cleave Connector
	P26764-01, LC Crimp & Cleave Connector
	P26764-02, LC Crimp & Cleave Connector
	P26764-03, LC Crimp & Cleave Connector
Connectors	
Connector Type	LC Duplex, LC Simplex
Connector Performance Data	
Operating Temperature	-40 to +85 °C
Crimp Retention	4.99 lb. (22.2 N)
Overall Length (With Boot Installed)	2.18 in. (55 mm)
Overall Length (Without Boot Installed)	1.53 in. (39 mm)
Insertion Loss 50/200/230 GiHCS®	Maximum @ 1300 nm, 1.7 dB
	Maximum @ 850 nm, 1.5 dB
	Typical @ 1300 nm, 1.2 dB
	Typical @ 850 nm, 1.0 dB
Insertion Loss 62.5/200/230 GiHCS	Maximum @ 1300 nm, 1.7 dB
	Maximum @ 850 nm, 1.5 dB
	Typical @ 1300 nm, 1.2 dB
	Typical @ 850 nm, 1.0 dB
Accessories	
Cleave Tool Cleaning Kit	P16247
Order by Part Number	DT03732-LC1

## For additional information please contact your sales representative.

You can also visit our website at www.ofsoptics.com or call 1-888-fiberhelp (1-888-342-3743) USA or 1-770-798-5555 outside the USA.







OFS Marketing Communications

Date: 01/20

HCS and GiHCS are registered trademarks of OFS Fitel, LLC. OFS reserves the right to make changes to the prices and product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any OFS warranties or specifications relating to any of its products or services.