



A Furukawa Company

Indoor/Outdoor Compact POE Module

for InvisiLight® Breezeway MDU Solution



External view of Indoor/Outdoor Compact POE Module



Internal view of Indoor/Outdoor Compact POE Module

Features

- Allows termination of the InvisiLight Multifiber unit through direct connectorization or splicing (fusion or mechanical) to optical extensions (pigtailed) of two optical fibers
- Accommodates one internal optical adapter (SC footprint)
- An access point in each side allows cable access from the top of the module
- InvisiLight Breezeway or jumper output occurs from the base of the module through two access points
- The multi-position adapter support allows the adapter to be housed in three different positions

Benefits

- Compact dimensions
- Discreet appearance
- UV-resistant material
- Easy to secure on the wall with two screws
- Internal fiber guides for easy installation
- Can be installed on any vertical plane surface
- Plastic body offers high mechanical resistance and an efficient design
- Accommodates splice protectors (40 mm)

Product Description

The Indoor/Outdoor Compact Point-of-Entry (POE) Module serves as the transition point between the building and the customer living unit. Following an installation survey, the installer mounts this module on the exterior wall of each living unit, in the breezeway, where the POE is protected from direct exposure to the elements. A fusion-spliced pigtail or mechanical connector connects the InvisiLight Multifiber Unit to the plug-and-play InvisiLight Indoor Living Unit (ILU) Solution. The Indoor/Outdoor Compact POE Module is part of the InvisiLight Multiple Dwelling Unit (MDU) Solution.



A Furukawa Company

Indoor/Outdoor Compact POE Module

Indoor/Outdoor Compact POE Module Specifications

Product Characteristics

Capacity	2 splices 1 adapter
Accessories	Screws and anchors
Application	Internal Use and Breezeway

Physical Characteristics

Dimensions (H x W x D)	1.6 in. x 6.0 in. x 0.63 in. (40.64 mm x 152.40 mm x 15.88 mm)
Material	Polypropylene (PP)
Color	Gray
Standards	RoHS

Indoor/Outdoor Compact POE Module Ordering Information

Part Number	Comcode	Description
NVSLGHTHO-CMODULE-GRAY-W/ SCA ADAPTER	301145751	Compact Point-of-Entry (POE) Module, Indoor/outdoor, gray, SCA
NVSLGHTHO-CMODULE-GRAY-W/ LCA ADAPTER	301152880	Compact Point-of-Entry (POE) Module, Indoor/outdoor, gray, LCA

For additional information please contact your sales representative.

You can also visit our website at www.ofsoptics.com or call 1-888-fiberhelp (1-888-342-3743) USA or 1-770-798-5555 outside the USA.



Copyright © 2019 OFS Fitel, LLC.
All rights reserved, printed in USA.

OFS Marketing Communications
DOC ID: fap-321 Date: 09/19



InvisiLight is a registered trademark of OFS Fitel, LLC.

OFS reserves the right to make changes to the prices and product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any OFS warranties or specifications relating to any of its products or services.