

## WE SERIES

The unique design of the WE Side Wall Mount allows servers to be mounted sideways, thus greatly reducing the amount of open area that is typically needed by other wall mounts and enclosures. This design also allows the WE to be mounted across three studs which provides extra stability. Three concentric knock-outs (1", 2", and 3") on the bottom, top, and rear of the enclosure support proper cable management. Lockable mesh side doors and an optional exhaust fan provide proper ventilation. A maximum rail spacing of 29" from front to rear creates 2" of space in front and 3" in the rear. *Mounted equipment shown for demonstration only. Wall Mount shown with locking front panel removed*



Drawings can be found on page 99



Equipment mounting hardware included • Color: Black

### PART NO. DESCRIPTION

**GL24WE** Dimensions 24.00"H x 36.10"W x 20.50"D, Usable space 34.00", Maximum rail spacing 29.00", Rack spaces 10 RMU, Wt. cap. 350 lbs., Shipping wt. 100 lbs., Mesh side doors and solid front panel; includes M6 cage nuts

### ACCESSORIES

#### PART NO. DESCRIPTION

7219 6 position Power Strip for 19" mounting; 5-15R receptacle and 5-15P plug  
 7219-SR14 14 position (6 front/8 back) Power Strip for 19" mounting; 5-15R receptacle and 5-15P plug  
 7217WS Fan Assembly with fan guards and two 75 CFM fans

## WR SERIES

Wall Rack Boxes allow the mounting of switches and sound equipment when space is limited. The boxes feature 19" EIA 310-D compliant mounting, #10-32 threaded mounting holes, and three position adjustable rails. Accessing equipment is convenient; A removable cover and keyhole wall mounting allows for left, right, or vertical equipment orientation. *Mounted equipment shown for demonstration only.*



Drawings can be found on page 100



### PART NO. DESCRIPTION

**WR2** Dimensions: 4.00"H x 19.75"W x 21.63"D, Usable space 21", Rack spaces: 2 RMU, Wt. cap. 50 lbs., Shipping wt. 17 lbs.

**WR4** Dimensions: 7.50"H x 19.75"W x 21.63"D, Usable space 21", Rack spaces: 4 RMU, Wt. cap. 75 lbs., Shipping wt. 20 lbs.

**CALL 1.866.TRY.GLCC (879-4522)**