

2-72 Fiber, Micro Distribution Aluminum Interlocking Armored Cable, Plenum

www.TheLightConnection.com

Features and Benefits

- Provides superior crush resistance for added protection
- Eliminates the need for inner duct or conduit thus saving installation time
- OFCR and OFCP ratings allow AIA products to be installed throughout the facility

Description

The Light Connection, Inc. 2 to 72 fiber Micro Distribution Aluminum Interlocking Armored cable consists of PVC overall jacket, PVC inner jacket with a standard TLC 2 to 72 fiber Micro Distribution core cable (Ask your TLC representative for core cable specifications). The Micro Distribution core cable is protected by a spirally-wrapped aluminum strip that offers easy installation and high crush resistance.

TLC Micro Distribution AIA Cable is available in 12 TIA standard colors or special-order colors. UL Listed OFCP cables are available, and unrated cables may be supplied to accommodate special needs. Standard surface print denotes construction, NEC rating, and fiber type, and includes footage markers.



Custom print may also be accommodated.

Application

Plenum

Flame Rating

NFPA 262



SPECIFICATIONS

Temperature Range

Storage Temperature	-40 C to +70 C
Operating Temperature	0 C to +70 C

Cable Characteristics

Fiber Count	2-72
Strength Member	Aramid Yarn
Overall Jacket Material	Poly Vinyl Chloride
Inner Jacket Material	Poly Vinyl Chloride
Armoring Material	Aluminum

Mechanical Characteristics

Value (2-12 / 24, 36 / 48 / 72 fiber count)

Nominal Outer Diameter (mm)	11.6 / 16.2 / 17.45 / 19.25
Bend Radius (cm)	23.2 / 32.4 / 34.9 / 38.5
Weight (lbs/ km)	274 / 490/ 641 / 833

Optical Characteristics

Items	Single Mode	OM1	OM2	OM3	OM4 (OM4+)	OM5 (WB MMF)
Core Size [μm]	9	62.5	50	50	50	50
Wavelength [nm]	1310/ 1550	850/ 1300	850/1300	850/ 1300	850/ 1300	850/ 1300
Max. Attenuation[dB/km]	0.5/ 0.4	3.5/ 1.5	3.5/1.5	3.0/ 1.0	3.0/ 1.0	3.0/ 1.0
Link Length[m]	10,000/5,000 (1/10Gb/s@1550nm)	300 (1Gb/s@850nm)	150 (10Gb/s@850nm)	300 (10Gb/s@850nm)	550(600) (10Gb/s@850nm)	550 (10Gb/s@850nm)
Bandwidth (EMB High Performance)[MHz.km]	–	220 @850	750@850	2,000 @850	4,700 @850	4,700@850

Part Numbers

Fiber Count	Single Mode	OM1	OM2	OM3-OM4	OM5
## (2 - 12)	S09MD##**NPY-AIA2	M62MD##**NPO-AIA2	M50MD##**NPO-AIA2	M50MD##**NPA-AIA2	M50MD##**NPLG-AIA2
## (24 - 36)	S09MD##**NPY-AIA2	M62MD##**NPO-AIA2	M50MD##**NPO-AIA2	M50MD##**NPA-AIA2	M50MD##**NPLG-AIA2
## (48 - 72)	S09MD##**NPY-AIA	M62MD##**NPO-AIA	M50MD##**NPO-AIA	M50MD##**NPA-AIA	M50MD##**NPLG-AIA

Fiber Type (9/125)	**
SMF-28 Ultra	CZ
ClearCurve LBL	C7
ClearCurve ZBL	CC

Fiber Type (50/125)	**
ClearCurve OM2	C2
Clear Curve OM3	CG
ClearCurve OM4	C4
ClearCurve OM5	C5

Fiber Type (62.5/125)	**
InfiniCor 300	C3



132 Base Road
Oriskany, NY, 13424
Phone: 315-736-7384
Fax: 315-736-1927
Toll free: 1-888-571-7111
sales@thelightconnection.com
www.thelightconnection.com