FAST ASSEMBLY AND OPEN DESIGN FOR QUICK EQUIPMENT INSTALLATION



Part No.	RMU	H" (mm)	W" (mm)	D" (mm)	Usable Depth in. (mm)	Max. Rail Depth in. (mm)	Airflow
GL06WMFP-B-00	6	12.65" (321)	23.62" (600)	17.12" (450)	16.73" (425)	15.19" (386)	Fan not included
GL06WMFP-B-AF	6	12.65" (321)	23.62" (600)	17.12" (450)	16.73" (425)	15.19" (386)	Fan Included
GL09WMFP-B-00	9	17.8" (454)	23.62" (600)	17.12" (450)	16.73" (425)	15.19" (386)	Fan not included
GL09WMFP-B-AF	9	17.8" (454)	23.62" (600)	17.12" (450)	16.73" (425)	15.19" (386)	Fan Included

FEATURES

- Fast and efficient assembly
- Flat packed for onsite storage
- Open design for easy equipment installation and maintenance
- · Reversible mesh door with locking cam
- · Hinged side panels (which can only be opened from inside) swing open 90 degrees and can be removed if necessary
- Two cable access knockouts on top and bottom
- 6" x 4" (153mm x x102mm) cable access on the rear
- · Load capacity 132 lbs (60kg)
- Color: Black





