

LV-Series Indoor/Outdoor Riser Loose Tube – Single Jacket

Indoor/outdoor stranded loose tube combines the robust mechanical and environmental characteristics of an outside plant cable with the flexibility of an inside plant riser cable. By installing an indoor/outdoor stranded loose tube, splice locations entering into a building are avoided, being routed directly from the outside plant to telecommunications closets, or main distribution frames (MDF) through the riser of a building and eliminating the “50-foot rule.” Indoor/Outdoor Stranded Design loose tube cable is moisture and U.V. resistant and is SZ stranded to allow slack for mid-span access.

Features

- Fiber counts up to 144
- Compact design
- Gel-filled or gel-free tubes are reverse-oscillated (SZ stranded) to allow slack for mid-span access

Applications


- Underground Duct
- Long Haul Networking
- Building Interconnections (Campus LAN)
- Trunking Lines Direct to Telecommunications Closet
- Local Loop
- Intrabuilding Backbones
- Distance Learning

Typical Lengths

FIBER COUNT	MAXIMUM LENGTHS*			
	SINGLE-MODE		MULTIMODE	
	feet	meters	feet	meters
6-144	22,900	7,000	22,900	7,000

* Longer lengths may be available.

Cable Components



Fiber Specifications

CORE SIZE/FIBER TYPE	AFL FIBER IDENTIFIER	ISO/IEC	MAXIMUM ATTENUATION (dB/km)				OVERFILL LAUNCH MIN. BANDWIDTH (MHz•km)		GIGABIT ETHERNET MAX. LINK DISTANCE (meters)	
			850 nm	1300 nm	1310 nm	1550 nm	850 nm	1300 nm	850 nm	1300 nm
62.5/125 GIGA-Link™ 300	6	OM1	3.5	1.2	N/A	N/A	200	600	300	550
50/125 GIGA-Link™ 600	5	OM2	3.5	1.5	N/A	N/A	500	500	600	600
50/125 Laser-Link™ 300	L	OM3	3.0	1.2	N/A	N/A	1500	500	1000	550
50/125 Laser-Link™ 300	C	OM4	3.0	1.2	N/A	N/A	3500	500	1040	550
Single-mode (ITU G.652.D/G.657.A1)	9	OS2	N/A	N/A	0.35	0.25	N/A	N/A	N/A	N/A
Corning Single-mode (ITU G.652.D/G.657.A1)	AZ	OS2	N/A	N/A	0.35	0.25	N/A	N/A	N/A	N/A

Gigabit Ethernet Minimum Link Distances are based on “bandwidth”/modal dispersion constraints. Actual link distances may be constrained by attenuation, depending on specific loss budget.

continued
→

LV-Series Indoor/Outdoor Riser Loose Tube – Single Jacket

Ordering Information

AFL NO.	FIBER COUNT	NUMBER OF TUBES/FIBERS	NOMINAL DIAMETER inches (mm)	NOMINAL WEIGHT lbs/1,000 ft (kg/km)	MAXIMUM TENSILE LOAD lbs (N)		MINIMUM BEND RADIUS inches (cm)	
					SHORT TERM	LONG TERM	SHORT TERM	LONG TERM
GEL-FILLED								
LV012★C5101N1	12	1w/12 (4 fillers)	0.51 (12.9)	108 (160)	600 (2700)	200 (890)	10.2 (26)	7.7 (20)
LV024★C5101N1	24	2w/12 (3 fillers)	0.51 (12.9)	108 (161)	600 (2700)	200 (890)	10.2 (26)	7.7 (20)
LV036★C5101N1	36	3w/12 (2 fillers)	0.51 (12.9)	109 (162)	600 (2700)	200 (890)	10.2 (26)	7.7 (20)
LV048★C5101N1	48	4w/12 (1 filler)	0.51 (12.9)	110 (164)	600 (2700)	200 (890)	10.2 (26)	7.7 (20)
LV060★C5101N1	60	5w/12 (No fillers)	0.51 (12.9)	111 (165)	600 (2700)	200 (890)	10.2 (26)	7.7 (20)
LV072★C6101N1	72	6w/12 (No fillers)	0.54 (13.7)	128 (190)	600 (2700)	200 (890)	10.8 (28)	8.1 (21)
LV096★C8101N1	96	8w/12 (No fillers)	0.61 (15.5)	159 (237)	600 (2700)	200 (890)	12.2 (31)	9.2 (24)
LV144★CC101N1	144	12w/12 (No fillers)	0.76 (19.3)	243 (361)	600 (2700)	200 (890)	15.2 (39)	11.4 (29)
GEL-FREE								
LV012★C5101N1D	12	1/12 (4 fillers)	0.48 (12.3)	100 (148)	600 (2670)	180 (800)	9.7 (25)	7.2 (19)
LV024★C5101N1D	24	2/12 (3 fillers)	0.48 (12.3)	99 (146)	600 (2670)	180 (800)	9.7 (25)	7.2 (19)
LV036★C5101N1D	36	3/12 (2 fillers)	0.48 (12.3)	99 (147)	600 (2670)	180 (800)	9.7 (25)	7.2 (19)
LV048★C5101N1D	48	4/12 (1 filler)	0.48 (12.3)	99 (147)	600 (2670)	180 (800)	9.7 (25)	7.2 (19)
LV060★C5101N1D	60	5/12 (no fillers)	0.48 (12.3)	98 (146)	600 (2670)	180 (800)	9.7 (25)	7.2 (19)
LV072★C6101N1D	72	6/12 (no fillers)	0.52 (13.1)	103 (154)	600 (2670)	180 (800)	10.3 (26)	7.8 (20)
LV096★C8101N1D	96	8/12 (no fillers)	0.58 (14.7)	138 (205)	600 (2670)	180 (800)	11.6 (29)	8.7 (23)
LV144★CC101N1D	144	12/12 (no fillers)	0.72 (18.2)	198 (295)	600 (2670)	180 (800)	14.3 (37)	10.8 (28)

Note: Diameter and weight subject to change without notice

★ Fiber Types – Replace asterisk (★) in AFL number with AFL Fiber Identifier in the Fiber Specifications table on previous page.

Reel Information

ITEM	REEL A		REEL B		REEL C		REEL D		REEL E	
	inches	cm	inches	cm	inches	cm	inches	cm	inches	cm
Reel Height	42	106.7	58	147.3	66	167.6	72	182.8	84	213.4
Reel Width Outside	36	91.4	38	96.5	42	106.7	42	106.7	40	101.6
Reel Width Inside	32	81.6	32	81.3	36	91.4	36	91.4	34	86.4
Drum Diameter	23	58.7	28	71.1	36	91.4	36	91.4	35	88.9
Arbor Hole Diameter	3	7.9	3	7.9	3	7.9	3	7.9	3	7.9
Reel Weight With Lagging	180 lbs	82 kg	420 lbs	191 kg	685 lbs	311 kg	710 lbs	320 kg	950 lbs	431 kg

AFL typically provides Loose Tube cable on several standard sizes of non-returnable wooden reels. Non-standard reel sizes are available upon request.

Larger reel sizes may be required to accommodate long cable lengths.

Qualifications

GOVERNING BODY	STANDARD CODE	COMPONENT
Telcordia	GR-20-CORE	Cable
UL	1666 (OFNR)	Cable
ICEA	S-104-696	Cable
CSA	22.2 (FT4)	Cable
TIA	598-D	Fiber

Temperature Specifications

TEMPERATURE RANGE	
OPERATION	-40°C to +70°C
STORAGE	-40°C to +70°C
INSTALLATION	-30°C to +70°C

Contact AFL for your customized cable solution.