

# 5519602 | QR® 715 JCAT Y

---

75 Ohm QR® Trunk and Distribution Cable, black PE jacket with co-extruded yellow stripe



## Product Classification

<b>Product Type</b>	Coaxial hardline cable
<b>Product Brand</b>	QR®

## General Specifications

<b>Cable Type</b>	715 Series
<b>Construction Type</b>	Welded
<b>Jacket Color</b>	Black with co-extruded yellow stripe
<b>Short Description</b>	QR 715 JCAT Y PR7344

## Dimensions

<b>Cable Length</b>	914.4 m   3000 ft
<b>Diameter Over Center Conductor, nominal</b>	4.216 mm   0.166 in
<b>Diameter Over Dielectric, nominal</b>	17.424 mm   0.686 in
<b>Diameter Over Jacket, nominal</b>	19.939 mm   0.785 in
<b>Diameter Over Outer Conductor, nominal</b>	18.161 mm   0.715 in
<b>Jacket Thickness, nominal</b>	0.889 mm   0.035 in
<b>Outer Conductor Thickness, nominal</b>	0.368 mm   0.014 in

## Electrical Specifications

<b>Capacitance</b>	50.197 pF/m   15.3 pF/ft
<b>Capacitance Tolerance</b>	±1.0 pF/ft
<b>Characteristic Impedance</b>	75 ohm
<b>Characteristic Impedance Tolerance</b>	±2 ohm
<b>dc Resistance Note</b>	Nominal values based on a standard condition of 20 °C (68 °F)

# 5519602 | QR® 715 JCAT Y

<b>dc Resistance, Inner Conductor, nominal</b>	1.903 ohms/km   0.58 ohms/kft
<b>dc Resistance, Loop, nominal</b>	3.281 ohms/km   1 ohms/kft
<b>dc Resistance, Outer Conductor, nominal</b>	1.378 ohms/km   0.42 ohms/kft
<b>Jacket Spark Test Voltage</b>	5000 Vac
<b>Nominal Velocity of Propagation (NVP)</b>	88 %
<b>Operating Frequency Band</b>	5–3000 MHz
<b>Structural Return Loss</b>	24 dB @ 1003–1218 MHz   24 dB @ 1219–1794 MHz   30 dB @ 5–1002 MHz
<b>Structural Return Loss, Grade N</b>	≥24 dB @ 1003–1218 MHz   ≥24 dB @ 1219–1794 MHz   ≥30 dB @ 5–1002 MHz

## Attenuation

Frequency (MHz)	Attenuation (dB/100 m)	Attenuation (dB/100 ft)
5.0	0.36	0.11
55.0	1.21	0.37
85.0	1.51	0.46
204.0	2.4	0.73
211.0	2.43	0.74
250.0	2.66	0.81
300.0	2.92	0.89
350.0	3.18	0.97
400.0	3.44	1.05
450.0	3.67	1.12
500.0	3.9	1.19
550.0	4.1	1.25
600.0	4.3	1.31
750.0	4.89	1.49
865.0	5.31	1.62
1002.0	5.76	1.75
1218.0	6.43	1.96
1500.0	7.44	2.27
1794.0	8.3	2.53
1800.0	8.32	2.54
2000.0	8.88	2.71
2200.0	9.42	2.87

# 5519602 | QR® 715 JCAT Y

---

<b>2500.0</b>	10.21	3.11
<b>2700.0</b>	10.72	3.27
<b>3000.0</b>	11.46	3.49

## Material Specifications

<b>Center Conductor Material</b>	Copper-clad aluminum
<b>Dielectric Material</b>	Foam PE
<b>Jacket Material</b>	PE
<b>Outer Conductor Material</b>	Aluminum

## Mechanical Specifications

<b>Minimum Bend Radius, bonded</b>	127 mm   5 in
<b>Pulling Tension, maximum</b>	154.221 kg   340 lb

## Environmental Specifications

<b>Environmental Space</b>	Aerial
----------------------------	--------

## Packaging and Weights

<b>Packaging Type</b>	Reel
<b>Weight, gross</b>	305.074 kg/km   205 lb/kft

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system