

75 Ohm P3® Trunk and Distribution Cable, black PE jacket



- *Product complies with the Build America, Buy America Act (BABAA) requirements of the Infrastructure Investment and Jobs Act of 2021 (Pub. L. 117- 58, §§ 70901-70953), or is the subject of a waiver approved by the Secretary of Commerce or designee. Compliance requirements and waiver applicability vary based on government funding program. Check the laws and regulations for your specific program.

Product Classification

Regional Availability	North America
Product Type	Coaxial hardline cable
Product Brand	P3®
Government Funding	Build America Buy America (BABA) compliant*
Warranty	One year

General Specifications

Cable Type	700 Series
Construction Type	Swaged
Jacket Color	Black
Short Description	P3 700 JCA SM PR2171

Dimensions

Cable Length	762 m 2500 ft
Diameter Over Center Conductor, nominal	4.14 mm 0.163 in
Diameter Over Dielectric, nominal	16.586 mm 0.653 in
Diameter Over Jacket, nominal	19.431 mm 0.765 in
Diameter Over Outer Conductor, nominal	17.856 mm 0.703 in
Jacket Thickness, nominal	0.787 mm 0.031 in
Outer Conductor Thickness, nominal	0.635 mm 0.025 in

Electrical Specifications

Capacitance	50.197 pF/m 15.3 pF/ft
Capacitance Tolerance	±1.0 pF/ft

5727603 | P3® 700 JCA

Characteristic Impedance	75 ohm
Characteristic Impedance Tolerance	±2 ohm
dc Resistance Note	Nominal values based on a standard condition of 20 °C (68 °F)
dc Resistance, Inner Conductor, nominal	1.936 ohms/km 0.59 ohms/kft
dc Resistance, Loop, nominal	2.756 ohms/km 0.84 ohms/kft
dc Resistance, Outer Conductor, nominal	0.82 ohms/km 0.25 ohms/kft
Jacket Spark Test Voltage	5000 Vac
Nominal Velocity of Propagation (NVP)	89 %
Operating Frequency Band	5–3000 MHz
Structural Return Loss	24 dB @ 1003–1218 MHz 24 dB @ 1219–1794 MHz 30 dB @ 5–1002 MHz
Structural Return Loss, Grade N	≥24 dB @ 1003–1218 MHz ≥24 dB @ 1219–1794 MHz ≥30 dB @ 5–1002 MHz

Attenuation

Frequency (MHz)	Attenuation (dB/100 m)	Attenuation (dB/100 ft)
5.0	0.36	0.11
55.0	1.18	0.36
85.0	1.51	0.46
204.0	2.4	0.73
211.0	2.4	0.73
250.0	2.66	0.81
300.0	2.95	0.9
350.0	3.22	0.98
400.0	3.45	1.05
450.0	3.67	1.12
500.0	3.9	1.19
550.0	4.1	1.25
600.0	4.3	1.31
750.0	4.89	1.49
865.0	5.32	1.62
1002.0	5.77	1.76
1218.0	6.43	1.96
1500.0	7.21	2.2
1794.0	7.98	2.43

5727603 | P3® 700 JCA

1800.0	8	2.44
2000.0	8.5	2.59
2200.0	8.98	2.74
2500.0	9.67	2.95
2700.0	10.11	3.08
3000.0	10.76	3.28

Material Specifications

Center Conductor Material	Copper-clad aluminum
Dielectric Material	Foam PE
Jacket Material	PE
Outer Conductor Material	Aluminum

Mechanical Specifications

Minimum Bend Radius, bonded	165.1 mm 6.5 in
Pulling Tension, maximum	226.796 kg 500 lb

Environmental Specifications

Environmental Space	Aerial
----------------------------	--------

Packaging and Weights

Packaging Type	Reel
Weight, gross	299.121 kg/km 201 lb/kft

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

