



FC/UPC to Stub, Tight Buffered Fiber, Riser Rated, 900um Singlemode 9/125um, Bend Insensitive, 8" Breakout

065-365-10-ML

## Product Description

How do you stand out from other Fiber Optic Assembly suppliers? By configuring your jumpers online and simply sending a RFQ. Our team is standing by to offer fast accurate quotes and initiate our quick ship program. Multilink's Surelight Connectivity Solutions incorporate Telcordia compliant components and meet or exceed GR326-CORE specifications. Our manufacturing process includes using bend insensitive fiber cable and endface geometry testing. From singlemode to multimode, our online fiber configurator offers a unique way for fast and accurate turn around, allowing more productivity in a day.

## Specifications

| Parameter                      | Specification    |
|--------------------------------|------------------|
| <b>Connector Type:</b>         | FC/UPC           |
| <b>Fiber Category:</b>         | Singlemode (OS1) |
| <b>Ferrule Material:</b>       | Zirconia         |
| <b>Housing Material:</b>       | Metal            |
| <b>Housing Color:</b>          | Metal            |
| <b>Boot Color:</b>             | Blue             |
| <b>Polish:</b>                 | UPC              |
| <b>Reflectance, Typical:</b>   | < -58 dB         |
| <b>Insertion Loss Typical:</b> | 0.12 dB          |

|                                  |   |
|----------------------------------|---|
| <b>Application:</b>              | Riser Rated<br>Indoor Vertical<br>General Building Applications               |
| <b>Cable Length:</b>             | 3 Meter   |
| <b>Cable Type:</b>               | (12) Singlemode 900µm Simplex 9/125µm Tight Buffered Bend Insensitive G657 A1 |
| <b>Flame Rating:</b>             | Riser Rated OFNR  |
| <b>Cable Assembly Type:</b>      | 12 Fiber Pigtail  |
| <b>Fiber Count:</b>              | 12  |
| <b>Outer Jacket Color:</b>       | Yellow  |
| <b>Nominal Outside Diameter:</b> | 6.35mm  |

**Contact Us**

| North America   | Europe, Middle East & Africa  | Latin & South America  |
|---|---|--|
| Tel: +1 440 366 6966<br>Fax: +1 440 366 6802<br>Email: <a href="mailto:engsupport@gomultilink.com">engsupport@gomultilink.com</a> | Tel: +1 440 366 6966<br>Fax: +1 440 366 6802<br>Email: <a href="mailto:engsupport@gomultilink.com">engsupport@gomultilink.com</a> | Tel: +1 954 499 9203<br>Mobile: +1 305 684 2388<br>Email: <a href="mailto:hquinones@gomultilink.com">hquinones@gomultilink.com</a> |

# **Multilink**®

*Innovation At Work*



Multilink Inc.  
 580 Ternes Ln  
 Elyria, OH 44035  
 Tel: (440) 366-6966  
 Fax: (440) 366-6802



[facebook.com/GoMultilink](https://facebook.com/GoMultilink)



[twitter.com/GoMultilink](https://twitter.com/GoMultilink)



[youtube.com/GoMultilink](https://youtube.com/GoMultilink)

© Multilink Inc. 2016 • All Rights Reserved

Contact Us |

| North America   | Europe, Middle East & Africa  | Latin & South America  |
|---|---|--|
| Tel: +1 440 366 6966<br>Fax: +1 440 366 6802<br>Email: <a href="mailto:engsupport@gomultilink.com">engsupport@gomultilink.com</a> | Tel: +1 440 366 6966<br>Fax: +1 440 366 6802<br>Email: <a href="mailto:engsupport@gomultilink.com">engsupport@gomultilink.com</a> | Tel: +1 954 499 9203<br>Mobile: +1 305 684 2388<br>Email: <a href="mailto:hquinones@gomultilink.com">hquinones@gomultilink.com</a> |