



LC/UPC to Stub, Tight Buffered Fiber, Riser Rated, OFNR FT-4, Multimode 62.5/125um, OM1, 8" Breakout

065-397-10-ML

## Product Description

How do you stand out from other Fiber Optic Assembly suppliers? By configuring your jumpers online and simply sending a RFQ. Our team is standing by to offer fast accurate quotes and initiate our quick ship program. Multilink's Surelight Connectivity Solutions incorporate Telcordia compliant components and meet or exceed GR326-CORE specifications. Our manufacturing process includes using bend insensitive fiber cable and endface geometry testing. From singlemode to multimode, our online fiber configurator offers a unique way for fast and accurate turn around, allowing more productivity in a day.

## Specifications

| Parameter                      | Specification   |
|--------------------------------|-----------------|
| <b>Connector Type:</b>         | LC/UPC          |
| <b>Fiber Category:</b>         | Multimode (OM1) |
| <b>Ferrule Material:</b>       | Zirconia        |
| <b>Housing Material:</b>       | Composite       |
| <b>Housing Color:</b>          | Beige           |
| <b>Boot Color:</b>             | White           |
| <b>Polish:</b>                 | UPC             |
| <b>Reflectance, Typical:</b>   | < -45 dB        |
| <b>Insertion Loss Typical:</b> | 0.20 dB         |

|                                  |  |
|----------------------------------|--|
| <b>Application:</b>              | Riser Rated<br>Indoor Vertical<br>General Building Applications        |
| <b>Cable Length:</b>             | 3 Meter  |
| <b>Cable Type:</b>               | Multimode 12 Fiber Distribution 62.5/125µm Tight Buffered<br>Fiber OM1 |
| <b>Flame Rating:</b>             | Riser Rated OFNR   |
| <b>Cable Assembly Type:</b>      | 12 Fiber Pigtail   |
| <b>Fiber Count:</b>              | 12   |
| <b>Outer Jacket Color:</b>       | Orange   |
| <b>Nominal Outside Diameter:</b> | 7.00mm   |

**Contact Us**

| North America   | Europe, Middle East & Africa  | Latin & South America  |
|---|---|--|
| Tel: +1 440 366 6966<br>Fax: +1 440 366 6802<br>Email: <a href="mailto:engsupport@gomultilink.com">engsupport@gomultilink.com</a> | Tel: +1 440 366 6966<br>Fax: +1 440 366 6802<br>Email: <a href="mailto:engsupport@gomultilink.com">engsupport@gomultilink.com</a> | Tel: +1 954 499 9203<br>Mobile: +1 305 684 2388<br>Email: <a href="mailto:hquinones@gomultilink.com">hquinones@gomultilink.com</a> |

# ***multilink***®

**Innovation At Work**



Multilink Inc.  
 580 Ternes Ln  
 Elyria, OH 44035  
 Tel: (440) 366-6966  
 Fax: (440) 366-6802



[facebook.com/GoMultilink](https://facebook.com/GoMultilink)



[twitter.com/GoMultilink](https://twitter.com/GoMultilink)



[youtube.com/GoMultilink](https://youtube.com/GoMultilink)

© Multilink Inc. 2016 • All Rights Reserved

| North America   | Europe, Middle East & Africa  | Latin & South America  |
|---|---|--|
| Tel: +1 440 366 6966<br>Fax: +1 440 366 6802<br>Email: <a href="mailto:engsupport@gomultilink.com">engsupport@gomultilink.com</a> | Tel: +1 440 366 6966<br>Fax: +1 440 366 6802<br>Email: <a href="mailto:engsupport@gomultilink.com">engsupport@gomultilink.com</a> | Tel: +1 954 499 9203<br>Mobile: +1 305 684 2388<br>Email: <a href="mailto:hquinones@gomultilink.com">hquinones@gomultilink.com</a> |

Contact Us |