

Splice-On Connector



Product Description

Using a factory terminated, pre-polished connector the Surelight® Splice-On Connector provides a connection meeting or exceeding industry standards for loss and back reflection. The Surelight® Splice-On Connector is provided with a factory cleaved 900um fiber stub to ensure easy of use and optimal performance. The unique 900um boot allows the entire splice to be concealed and protected, allowing for a simpler cable management system within the rack or enclosure. To terminate, just remove the cleave protector, place the connector into the holder, place the holder in the splicer, load the prepared field fiber into splicer and the connector is ready to be terminated.

Features & Benefits

900um boot protects splice for easy cable management

Includes color coded 900um buffer, boot, cleave protector and extended dust cap for easy fiber identification

Universal holders for multiple fusion splicers

Specifications

General Specifications	
Parameter	Specification
Connector Type:	SC/UPC
Quantity:	10 pack
Insertion Loss(Max):	>65dB >55dB
Ferrule Type:	All Zirconia Pre-Polished Ferrules
Operating Temperature:	-40 to +85 Degrees C
Standards:	RoHS Compliant, Telcordia GR-326-CORE Compliant
Cable Retention:	2.5 lbs.

Multilink®

Innovation At Work



Multilink Inc.
580 Ternes Ln
Elyria, OH 44035
Tel: (440) 366-6966
Fax: (440) 366-6802



facebook.com/GoMultilink1



twitter.com/GoMultilink



youtube.com/GoMultilink

© Multilink Inc. 2019 • All Rights Reserved