



LC/UPC to LC/UPC, Tight Buffered Cable, Riser Rated, 3.0mm, Multimode 62.5/125um, OM1

10-6291-ML

## Product Description

How do you stand out from other Fiber Optic Assembly suppliers? By configuring your jumpers online and simply sending a RFQ. Our team is standing by to offer fast accurate quotes and initiate our quick ship program. Multilink's Surelight Connectivity Solutions incorporate Telcordia compliant components and meet or exceed GR326-CORE specifications. Our manufacturing process includes using bend insensitive fiber cable and endface geometry testing. From singlemode to multimode, our online fiber configurator offers a unique way for fast and accurate turn around, allowing more productivity in a day.

## Specifications

| Parameter               | Specification   |
|-------------------------|-----------------|
| Connector Type:         | LC/UPC          |
| Fiber Category:         | Multimode (OM1) |
| Ferrule Material:       | Zirconia        |
| Housing Material:       | Composite       |
| Housing Color:          | Beige           |
| Boot Color:             | White           |
| Insertion Loss Typical: | 0.20 dB         |

|                                  |  |
|----------------------------------|--|
| <b>Application:</b>              | Riser Rated<br>Indoor Vertical<br>General Building Applications    |
| <b>Cable Length:</b>             | 5 Meter  |
| <b>Cable Type:</b>               | Multimode 3.0mm Duplex Zipcord 62.5/125µm Tight Buffered Fiber OM1 |
| <b>Flame Rating:</b>             | Riser Rated OFNR   |
| <b>Cable Assesmbly Type:</b>     | Duplex Fiber   |
| <b>Fiber Count:</b>              | 2  |
| <b>Outer Jacket Color:</b>       | Orange   |
| <b>Nominal Outside Diameter:</b> | 3.6mm  |
| <b>Polish #1:</b>                | UPC  |
| <b>Reflectance, Typical #1:</b>  | < -45 dB   |
| <b>Polish #2:</b>                | UPC  |
| <b>Reflectance, Typical #2:</b>  | < -45 dB   |

**Contact Us**

| North America   | Europe, Middle East & Africa  | Latin & South America  |
|---|---|--|
| Tel: +1 440 366 6966<br>Fax: +1 440 366 6802<br>Email: <a href="mailto:engsupport@gomultilink.com">engsupport@gomultilink.com</a> | Tel: +1 440 366 6966<br>Fax: +1 440 366 6802<br>Email: <a href="mailto:engsupport@gomultilink.com">engsupport@gomultilink.com</a> | Tel: +1 954 499 9203<br>Mobile: +1 305 684 2388<br>Email: <a href="mailto:hquinones@gomultilink.com">hquinones@gomultilink.com</a> |

# **multilink**®

*Innovation At Work*



Multilink Inc.  
 580 Ternes Ln  
 Elyria, OH 44035  
 Tel: (440) 366-6966  
 Fax: (440) 366-6802



[facebook.com/GoMultilink](https://facebook.com/GoMultilink)



[twitter.com/GoMultilink](https://twitter.com/GoMultilink)



[youtube.com/GoMultilink](https://youtube.com/GoMultilink)

© Multilink Inc. 2016 • All Rights Reserved

| North America   | Europe, Middle East & Africa  | Latin & South America  |
|---|---|--|
| Tel: +1 440 366 6966<br>Fax: +1 440 366 6802<br>Email: <a href="mailto:engsupport@gomultilink.com">engsupport@gomultilink.com</a> | Tel: +1 440 366 6966<br>Fax: +1 440 366 6802<br>Email: <a href="mailto:engsupport@gomultilink.com">engsupport@gomultilink.com</a> | Tel: +1 954 499 9203<br>Mobile: +1 305 684 2388<br>Email: <a href="mailto:hquinones@gomultilink.com">hquinones@gomultilink.com</a> |

Contact Us