



SC/UPC to LC/UPC, Tight Buffered Cable, Riser
Rated, 3.0mm, Singlemode 9/125um

10-6399-ML

Product Description

How do you stand out from other Fiber Optic Assembly suppliers? By configuring your jumpers online and simply sending a RFQ. Our team is standing by to offer fast accurate quotes and initiate our quick ship program. Multilink's Surelight Connectivity Solutions incorporate Telcordia compliant components and meet or exceed GR326-CORE specifications. Our manufacturing process includes using bend insensitive fiber cable and endface geometry testing. From singlemode to multimode, our online fiber configurator offers a unique way for fast and accurate turn around, allowing more productivity in a day.

Specifications

| Parameter | Specification |
|----------------------------|------------------|
| Connector Type: | SC/UPC LC/UPC |
| Fiber Category: | Singlemode (OS1) |
| Ferrule Material: | Zirconia |
| Housing Material: | Composite |
| Housing Color: | Blue |
| Boot Color: | Blue White |
| Insertion Loss Typical: | 0.12 dB |

| | |
|----------------------------------|------------------------------------------------------------------------------------|
| Application: | Riser Rated Indoor Horizontal General Building Applications |
| Cable Length: | 10 Meter |
| Cable Type: | Singlemode 3.0mm Duplex Zipcord 9/125µm Tight Buffered Bend Insensitive G657 A1 |
| Flame Rating: | Riser Rated OFNR |
| Cable Assesmbly Type: | Duplex Fiber |
| Fiber Count: | 2 |
| Outer Jacket Color: | Yellow |
| Nominal Outside Diameter: | 3.6mm |
| Polish #1: | UPC |
| Reflectance, Typical #1: | < -58 dB |
| Polish #2: | UPC |
| Reflectance, Typical #2: | < -58 dB |

Contact Us

| North America | Europe, Middle East & Africa | Latin & South America |
|-----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| Tel: +1 440 366 6966 Fax: +1 440 366 6802 Email: engsupport@gomultilink.com | Tel: +1 440 366 6966 Fax: +1 440 366 6802 Email: engsupport@gomultilink.com | Tel: +1 954 499 9203 Mobile: +1 305 684 2388 Email: hquinones@gomultilink.com |

multilink®

Innovation At Work



Multilink Inc.
 580 Ternes Ln
 Elyria, OH 44035
 Tel: (440) 366-6966
 Fax: (440) 366-6802



facebook.com/GoMultilink



twitter.com/GoMultilink



youtube.com/GoMultilink

© Multilink Inc. 2016 • All Rights Reserved

| North America | Europe, Middle East & Africa | Latin & South America |
|-----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| Tel: +1 440 366 6966 Fax: +1 440 366 6802 Email: engsupport@gomultilink.com | Tel: +1 440 366 6966 Fax: +1 440 366 6802 Email: engsupport@gomultilink.com | Tel: +1 954 499 9203 Mobile: +1 305 684 2388 Email: hquinones@gomultilink.com |

Contact Us |