

# 760253648 | 26" Pole Cab with Tapered Fluted Shaft



Bottom of the Pole, 26in Square base with round tapered fluted shaft 4G/5G/mmWave Concealment Enclosure to house and conceal multiple low to high power radios and other wireless infrastructure equipment in a cabinet at the base of the pole.

- Intended to house and conceal multiple radios and any other wireless infrastructure equipment in a cabinet at the base of the pole
- Flexible configuration accepts low to high-power single or dual band radios, Integrated AC load center/OVP and Disconnect and integrated AC/DC rectifier options

Supports 4G and mmWave/5G mounting  
Decorative arm and light not included

## OBSOLETE

### Replaced By:

760253649

30" Pole Cab with Tapered Fluted Shaft

Bottom of the Pole 30in Square base with round tapered fluted shaft 4G/5G/mmWave Concealment Enclosure to house and conceal multiple low to high power radios and other wireless infrastructure equipment in a cabinet at the base of the pole.

## Product Classification

<b>Portfolio</b>	CommScope®
<b>Product Type</b>	Pole cab
<b>Product Brand</b>	Metro Cell
<b>Ordering Note</b>	CommScope® standard product with terms
<b>Warranty</b>	One year

## General Specifications

<b>Color Options</b>	Black (RAL 9005)
<b>Compatible Foundation Type</b>	Poured Concrete   Pre-Cast Concrete
<b>Compatible Smart Devices</b>	Cameras   Digital Signage   Emergency Call Station   Environmental Monitoring   Security Lighting   WIFI
<b>Cooling</b>	Fan Cooling
<b>Power Supply Compatibility</b>	ABB CC1600   CCI PSU-1200W-48-N   DELTA 2.0   PSU-AC-08
<b>Radio Compatibility, Ericsson</b>	(1) 8843/4449 dual-band high power radio and (2) PSU-AC08   220x   440x
<b>Radio Compatibility, Nokia</b>	AHFIA   AHFIB   AHIA   AHIB   AHLBA   AHLBBA   AZRB   Aircscale micro
<b>Radio Compatibility Samsung</b>	RF4402D-D1A   RT2201-46A   RT4401-48A

# 760253648 | 26" Pole Cab with Tapered Fluted Shaft

---

**Radios Included** None

## Dimensions

**Height Note** 4 ft tall Equipment Cabinet Base

**Pole Height Options** 8.839 m | 29 ft

**Width** 660.4 mm | 26 in

**Depth** 660.4 mm | 26 in

**Depth Note** Square

**Pole Diameter** 203.2 mm | 8 in

## Electrical Specifications

**Power/Fiber Input** AC load center with OVP and disconnect | Fiber demarcation

## Material Specifications

**Finish Aluminum** Chromate

**Finish Concealment Covers** Powder coated

**Material Type** Galvanized steel | Steel

## Environmental Specifications

**Thermal Compliance** GR-487

## \* Footnotes

**Warranty** For more information, please consult our Product Warranty guidelines

**Pole Height Options** Overall AGL Standard Height