## S14B0-T3-A00D00-00 | CMC14S



CMC14S Equipment Thermosiphon Empty Micro Cell Site Cabinet

The cabinet is designed to house rack mounted equipment. This includes DC power systems, Fiber storage/splice trays, cell site routers, batteries, and other rack mounted equipment. This cabinet provides mechanical and environmental protection for the equipment inside. Cooling of active equipment is achieved by DC rated 100W/k Thermosiphon.

- Excellent Thermal Performance compatible with a thermosiphon
- Provides mounting space for power distribution, network servers, batteries, or other equipment.
- Front door compatible with Pad Lock.
- Provides flexible access for the cable entrances.
- Optional heater for cold environments.
- Provides 14RU of 19" Rack Space for Equipment
- Common parts available across the same platform.

## Product Classification

Product Type Outdoor cabinet

Product Series CMC

## General Specifications

**Access** Front door | Removable panel

Alarm Type Door alarm | HVAC alarms (including high temperature, failure) | S2 module, 20P or

standard and user defined alarms

**Batteries** Not included

Batteries Supported 6

Capacity 500W Heater

**Color** Gray

**Cooling** 100 W/k Thermosiphon

**Door Security**Quarter turn lock, puck lock system for rear door | Swing handle, puck lock system for front

door

Mounting H-frame | Pad | Pole | Universal wall mount

Page 1 of 2



## S14B0-T3-A00D00-00 | CMC14S

Noise Emission, maximum 65 dBA

Rack Type EIA 19 in

Rack Units 14

**Dimensions** 

 Height
 812.8 mm | 32 in

 Width
 609.6 mm | 24 in

 Depth
 558.8 mm | 22 in

**Electrical Specifications** 

Battery String Current, maximum 100 A-h @ -48 Vdc

**Battery Strings, quantity** 2 @ -48 Vdc **Cooling Capacity** 1000 W

**dc Distribution Type** 19" Rack DC Distribution Panels or DIN Breakers

Voltage -48 Vdc

Material Specifications

**Finish** Powder coated | UV resistant

Material Type Aluminum

**Environmental Specifications** 

Operating Temperature  $-40 \,^{\circ}\text{C}$  to  $+46 \,^{\circ}\text{C}$  (-40  $^{\circ}\text{F}$  to +115  $^{\circ}\text{F}$ )

Storage Temperature  $-40 \,^{\circ}\text{C}$  to  $+70 \,^{\circ}\text{C}$  (-40  $^{\circ}\text{F}$  to +158  $^{\circ}\text{F}$ )

Environmental Space UV resistant for outdoor

Qualification Standards IP55 | Telcordia GR-487

Thermal Compliance GR-487

Packaging and Weights

**Weight, net** 45.359 kg | 100 lb

Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

