

# 760062356 | PM-GS3-24 w/Termination Mgt.



GigaSPEED XL® PATCHMAX® GS3 Category 6 U/UTP Copper Patch Panel, 24 port with termination manager

- Available for use with the DYMO® labeling solution

## Product Classification

### Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North America

### Portfolio

SYSTIMAX®

### Product Type

RJ45 patch panel

### Product Brand

GigaSPEED XL® | PATCHMAX®

## General Specifications

### ANSI/TIA Category

6

### Cable Type

Unshielded

### Color

Black

### Conductor Type

Solid | Stranded

### Intelligence Type

Passive

### Modules, quantity

4

### Rack Type

EIA 19 in

### Rack Units

2

### Termination Type

IDC

### Total Ports, quantity

24

### Transmission Standards

ANSI/TIA-568-D.2 | ISO/IEC 11801 Class E

### Wiring

T568A | T568B

## Dimensions

### Height

89.66 mm | 3.53 in

### Width

482.6 mm | 19 in

### Depth, with cable management

206.5 mm | 8.13 in

### Compatible Diameter Over Dielectric, maximum

1.168 mm | 0.046 in

### Compatible Diameter Over Dielectric, minimum

0.762 mm | 0.03 in

### Compatible Conductor Gauge, solid

22-24 AWG | 21 AWG (for CommScope GigaREACH cable)

# 760062356 | PM-GS3-24 w/Termination Mgt.

<b>Compatible Conductor Gauge, stranded</b>	only) 22–24 AWG
<b>Electrical Specifications</b>	
<b>Current Rating at Temperature</b>	1.5 A @ 20 °C   1.5 A @ 68 °F
<b>Dielectric Withstand Voltage, RMS, conductive surface</b>	1,500 Vac @ 60 Hz
<b>Dielectric Withstand Voltage, RMS, contact-to-contact</b>	1,000 Vac @ 60 Hz
<b>Insulation Resistance, minimum</b>	500 MOhm
<b>Remote Powering</b>	Fully complies with the recommendations set forth by IEEE 802.3bt (Type 4) for the safe delivery of power over LAN cable when installed according to ISO/IEC 14763-2, CENELEC EN 50174-1, CENELEC EN 50174-2 or TIA TSB-184-A

## Material Specifications

<b>Contact Plating Material</b>	Precious metals
<b>Material Type</b>	High-impact, flame retardant, thermoplastic   Powder-coated steel
<b>Termination Contact Plating</b>	Nickel

## Mechanical Specifications

<b>Plug Insertion Life, minimum</b>	750 times
<b>Plug Insertion Life, test plug</b>	IEC 60603-7 compliant plug
<b>Plug Retention Force, minimum</b>	133 N   29.9 lbf

## Environmental Specifications

<b>Operating Temperature</b>	-10 °C to +60 °C (+14 °F to +140 °F)
<b>Storage Temperature</b>	-40 °C to +70 °C (-40 °F to +158 °F)
<b>Relative Humidity</b>	Up to 95%, non-condensing
<b>Flammability Rating</b>	UL 94 V-0
<b>Safety Standard</b>	UL   cUL

## Packaging and Weights

<b>Packaging quantity</b>	1
---------------------------	---

## Regulatory Compliance/Certifications

Agency	Classification
--------	----------------

# 760062356 | PM-GS3-24 w/Termination Mgt.

---

CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a>
ROHS	Compliant
UK-ROHS	Compliant

