CS1927-000 | FOSC-OSKG



FOSC® Gel Sealing Kit for oval splice closure port, sealing 1 looped cable with diameter between 5 and 15 mm

- Unique gel-based mechanical sealing option used on fiber splice closure ports for blown, standard, mini- and micro-cables
- Allows usage of multiple cable drops in a single closure outlet port, thus significantly increasing existing cable capacity
- Ideal for fiber cables with thin outer jackets that are difficult to seal with standard heat shrinkable sleeves

Product Classification

Regional Availability	EMEA
Product Type	Cable sealing
Product Brand	FOSC®
Product Series	FOSC 400G
General Specifications	
Application	For use with FOSC-400G Fiber closures
Cable Capacity, maximum	1
Color	Black
Dimensions	
Single Cable Diameter, maximum	15 mm 0.591 in
Single Cable Diameter, minimum	5 mm 0.197 in
Packaging and Weights	
Included	Cable termination brackets Dummy plugs Multi-out gel seal
Packaging quantity	1

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant

Page 1 of 2

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: July 17, 2024



CS1927-000 | FOSC-OSKG



Compliant



©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: July 17, 2024

