

# PROPEL-PANELS

---

## Base Product



Propel Series Sliding Fiber Optic Panels for holding Propel modules, adapter packs and splice cassettes

- Any size Propel component can be used in each panel or blade
- Components can be installed and removed from front or rear of panel
- Supports 8f, 12f, 16f and 24f applications while maintaining full panel density
- Cable mounting system allows for multiple trunk cables to be securely attached in the rear of panel

Propel high-density panels are designed to adapt and grow as your needs change. Like all Propel components, the panels are completely modular and interchangeable. They support 8-12-16-24-fiber Ultra Low Loss MPO connectivity and up to 144 LC-connected fibers per RU—giving you the flexibility and density to seamlessly advance to 100Gb, 400Gb, 800Gb and beyond without the need to change panels on site.

## Product Classification

<b>Regional Availability</b>	Asia   Australia/New Zealand   EMEA   Latin America   North America
<b>Portfolio</b>	SYSTIMAX®
<b>Product Type</b>	Fiber patch panel
<b>Product Brand</b>	Propel
<b>Product Series</b>	PPL

## General Specifications

<b>Color</b>	Gray
<b>Rack Type</b>	EIA 19 in

# PROPEL-PANELS

---

## Port Configuration

Panel size	8-fiber components	12-fiber components	16-fiber components	24-fiber components
1RU	up to 6 per blade	up to 4 per blade	up to 3 per blade	up to 2 per blade
2RU	up to 6 per blade	up to 4 per blade	up to 3 per blade	up to 2 per blade
4RU	up to 6 per blade	up to 4 per blade	up to 3 per blade	up to 2 per blade
<b>Each blade has 12 lanes</b>				
	Requires 2 lanes	Requires 3 lanes	Requires 4 lanes	Requires 6 lanes

## Environmental Specifications

**Safety Standard**            c-UL-us